# **Serenity SERS9440**

(1) 115v 20AMP GFCI Circuits

PRODUCT NUMBER: SERS9440 ... D A

4"	Χ	40"	Х	22"			
----	---	-----	---	-----	--	--	--

TECHNICAL SPECIFICATIONS						
Drain	End drain					
Pump Location(s): Select 1	Std. = Standard / Alt LF/RF Optional					
Bath Weight (empty)	215 lbs					
Gallons to Operate	85-110					
ELECTRICAL SPECIFICATIONS						

# ReVive Silver Oxygen Soak Series



BATHERS: 1						
INSTALLATION						
•	DECK (D)					
	UNDER MOUNT (U)					
	ALCOVE (A)					
	FREESTANDING (F)					
	CLAWFOOT (L)					
	PEDESTAL (P)					



## STANDARD FEATURES & ACCESSORIES

#### **PUMPS**

Oxygen Pressure Pump Quiet Pad Anti-Vibration Mounted Pump

#### **CONTROLS**

Motor/Pump

Air Switch On/Off Control(s) for Hydro Pump

#### **PURITY**

HydroCleanse

## STANDARD ACCESSORIES

EZ Clean Cast Acrylic FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily) 30 Point Quality Assurance Factory Test EZ Level Adjustable Legs

## **OPTIONAL FEATURES & ACCESSORIES**

Hair and Facial Wand

#### **COLOR**

Only Available in White

## REQUIREMENTS

Pump Locations: Select 1

Electrical: one 115v 20AMP GFCI Circuits


Tub should not be supported by the lip in any way. Level tub & screw or glue EZ Level adjustable legs to sub floor. **CUT OUT DIMENSIONS:** 

**OVALS:** A template will be provided


**RECTANGLES:** Subtract 1" to 1.5" from length & width for hole cut out size


**EZ CLEAN CAST ACRYLIC** LIMITED LIFETIME WARRANTY





Bath include EZ Level Legs **INSTALLATION WILL NOT REQUIRE MORTAR BEDDING** 





NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site. Access 18"x 18" or larger is required for each pump. Some pump locations and plumbing may extend beyond the perimeter of the bath.

radius corner lip profile