Sarah 5833SD | Air A34 Massage Series

Product Number: SRA34J5833SDFS-A 58" x 33" x 27"







STANDARD & OPTIONAL ACCESSORIES

JETS: 34 Total

- X 18 EZ Clean HTT Air Jets
- X 10 EZ Clean HTT Leg Therapy Air Massage Jets
- X 6 EZ Clean HTT Back Therapy Air Massage Jets

PUMPS 💠

1.25 Air Power Variable Speed, Pulse & Wave Heated Air Pump Quiet Pad Anti-Vibration Mounted Pumps

Whisper Flo Heat Pump System with Control & Ecobond Foam Insulation (must select Pump Locations)

HEATERS

Heated Air Pump • Whisper Flo Heat System Warm Back Rest Tubing Zone

CONTROLS

Air Switch On/Off Control(s) for Chromatherapy & Whisper Flo Heat Pump Variable Speed Air Massage Control Automatic Purge & Dry Cycle Control

PURITY

HydroCleanse

DRAINS & OVERFLOWS INFORMATION

- Overflow: Integral Slotted in Acrylic no finishes available
- Bath Drain: Pop up: Included- Polished Chrome or Brushed Nickel.

Optional-White, Biscuit, Black, Polished Nickel, Oil Rubbed Bronze.

• In Floor Drain EZ Fast Connect (optional)

FAUCET INFORMATION

- Deck Mount or Floor mount (not included & no faucet holes drilled)
- Access Panel recommended for Deck faucet (optional)
- · Floor mount verify spout distance

STANDARD ACCESSORIES

Grab Bar(s) - 2 on End Drain baths - White, Biscuit, Bone, Brushed Nickel. Polished Chrome. Oil Rubbed Bronze


Chromatherapy Lighting • Deluxe Cushion Pillow • EZ Level Base • FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily) • 30 Point Quality Assurance Factory Test

ADDITIONAL INFORMATION

6 1/2" or more space required to access equipment panel. Tub may also need to be shifted or disconnected in some situations.

Access panel equipment design and location may vary based on model.

Your qualified installer must water test and run all equipment before leaving your home to ensure proper operation and validate warranty.



TECHNICAL SPECIFICATIONS

Side drain

Pump Location(s): Standard or #2RF

ELECTRICAL REQUIREMENTS

(2) 115v 20AMP GFCI Circuits



