Zen ZECP6636SD

66" x 36" x 23"

PRODUCT NUMBER: ZECP6636SD ... D ... D ...

TECHNICAL SPECIFICATIONS					
Drain	Side drain				
Pump Location(s): Select 3	Std. = Standard / Alt LF/RF Optional				
Bath Weight (empty)	165 lbs				
Gallons to Operate	53-78				
ELECTRICAL SPECIFICATIONS					

Pump Location(s): Select 3 Std. = Standard / Alt LF/RF Optional		•	DECK (D)
Bath Weight (empty) 165 lbs		$\cdot \mid$	UNDER MOUNT (L
Gallons to Operate 53-78		·	ALCOVE (A)
ELECTRICAL SPECIFICATIONS			FREESTANDING (
Motor/Pump (3) 115v 20AMP GFCI Circuits			CLAWFOOT (L)
nline Stainless Steel Heater (1) 115v 20AMP GFCI Circuit			PEDESTAL (P)

COMBINATION PLATINUM SERIES Jet & Control



STANDARD FEATURES & ACCESSORIES for COMBINATION PLATINUM SERIES BATHS

M

38 Air & Water Massage Jets Back Massage System(s) (7 Jets) Neck Massage Pillow (2 Jets) (⊕⊕) Sole Soother Jet(s) Accumassage Back & Neck Jets ⊕ Ultra Flow Jets - 0-Classic Air Jets () EZ Clean Air Jets (optional) X

PUMPS

Two-3.25 Hydropower 3-speed Pumps 1.25 Air Power Variable Speed, Pulse & Wave heated Air Pump Quiet Pad Anti-Vibration Mounted Pump

HEATERS

Stainless Steel Heater Warm Back Rest Tubing Zone

CONTROLS


Air Switch On/Off for Chromatherapy Lighting Air Switch On/Off with digital Temperature Readout Hydro Pumps Electronic Variable Speed Air Massage Control with Automatic Purge & Dry Cycle Control Air Pump 3 Speed Massage: High, Medium or Low

PURITY

8.5

HydroClean Water Purity System HydroCleanse

OPTIONAL FEATURES & ACCESSORIES (Please type in the box below)



INSTALLATION WILL NOT REQUIRE MORTAR BEDDING

STANDARD ACCESSORIES

Grab Bar(s) - 1 on Side Drain Baths

White, Biscuit, Bone, Brushed Nickel, Polished Chrome

placement may vary

Chromatherapy Lighting

Deluxe Cable Drain - White, Biscuit, Bone, Brushed Nickel,

Oil Rubbed Bronze, Polished Chrome

Deluxe Cushion Pillow on 2 person baths

Neck Massage Pillow

EZ Level Base

BATHERS: 2

INSTALLATION

FDA Recipe Non-Toxic Food & Beverage Grade Plumbing (primarily) 30 Point Quality Assurance Factory Test

REQUIREMENTS

Pump Locations: Select 3

Electrical: Four 115v 20AMP GFCI Circuits Cable Drain and Grab Bars: Select Color / Finish Tub should not be supported by the lip in any way.

Level tub & screw or glue EZ Level adjustable legs to sub floor.

CUT OUT DIMENSIONS:


OVALS: A template will be provided


RECTANGLES: Subtract 1" to 1.5" from length & width for hole cut out size

LIMITED LIFETIME WARRANTY **TEXTURED FLOOR**



- A X HTT® Leg Therapy Air Massage System includes 10 Air Jets on the floor. Optional on Combo Plat and Combo Gold Series
- B X 6 Jet HTT® Back Massage System: N/A on Combo Series-Standard on Plat series
- **☼** Warm Back Tubing Zone





Some standard & most alternate pump locations may stickout past perimeter of the bath 1"-3". NOTE: Graphics may not be to scale. Specifications and features are subject to change without notice and are ± .25". All final measurements should be taken from tub on site. Access 18"x 18" or larger is required for each pump. Consult your contractor for installation requirements.